

Compressed Air Supply – From a Single Source

As a specialist in compressed air braking systems, WABCO offers you a comprehensive assortment of air reservoirs, retaining straps and drainage valves.

All reservoirs comply with the required European standard EN 286 and are available in the usual WABCO original quality.

The following overview includes an excerpt from our air reservoir and retaining strap range.



The table columns show reservoirs sorted by outer diameter (columns) and reservoir volume (rows). Both the length (L) and maximum operating pressure (in bar) are specified for each product. The retaining straps in the bottom row fit all reservoirs in the column. The connections of the reservoirs are all listed in M 22x1.5.

D= V=	Ø 206	Ø 246	Ø 276	Ø 310	Ø 396
10 l	950 410 004 0 L=368 15.5bar				
15 l	950 415 005 0 L=527 15.5bar	950 515 003 0 L=384 16.5bar			
20 l	950 420 003 0 L=691 15.5bar	950 520 003 0 L=495 15.5bar	950 720 005 0 L=414 14.5bar		
30 l	950 430 001 0 L=991 15.5bar	950 530 002 0 L=709 15.5bar	950 730 007 0 L=583 14.5bar		
40 l		950 540 001 0 L=927 15.5bar	950 740 002 0 L=758 14.5bar	950 740 906 0 L=618 12.5bar	
60 l			950 760 002 0 L=1108 14.5bar	950 060 003 0 L=893 12.5bar	950 060 004 0 L=580 12.5bar
80 l					950 080 002 0 L=750 12.5bar
100 l					950 100 002 0 L=915 12.5bar
	Clamping band 451 999 206 2	Clamping band 451 999 246 2	Clamping band 451 999 276 2	Clamping band 451 999 310 2	Clamping band 451 999 396 2

Please contact your personal WABCO contact person for an overview of all steel and aluminium air reservoirs.

All aforementioned reservoirs can be fitted with the following drainage valves:

Product number	Thread	Operation	Comment
934 300 001 0	M 22x1.5	Manual	without ring
934 300 003 0	M 22x1.5	Manual	with ring
934 301 000 0	M 22x1.5	Automatic	Delta p < 0.4 bar
934 301 003 0	M 22x1.5	Automatic	Delta p = 0.5±0.2 bar